

US009095396B2

(12) United States Patent

Collins et al.

(54) POROUS IMPLANT WITH NON-POROUS THREADS

(75) Inventors: Michael Scott Collins, San Marcos, CA

(US); Jeffrey Bassett, Vista, CA (US); Steven Pelote, Vista, CA (US); Joseph A. Salvi, Chula Vista, CA (US);

Shahram Zamani, San Diego, CA (US); Mojtaba Esfahani, Del Mar, CA (US)

(73) Assignee: Zimmer Dental, Inc., Carlsbad, CA

(US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 13/561,831

(22) Filed: Jul. 30, 2012

(65) **Prior Publication Data**

US 2013/0022943 A1 Jan. 24, 2013

Related U.S. Application Data

- (63) Continuation-in-part of application No. 12/167,107, filed on Jul. 2, 2008, now Pat. No. 8,231,387.
- (51) Int. Cl. *A61C 8/00* (2006.01)

(58) Field of Classification Search

(10) Patent No.:

US 9,095,396 B2

(45) **Date of Patent:** *Aug. 4, 2015

(56) References Cited

U.S. PATENT DOCUMENTS

1,929,425 A 10/1933 Hermann 2,721,387 A 10/1955 Ashuckian (Continued)

FOREIGN PATENT DOCUMENTS

CA 2506845 A1 7/2004 CA 2506854 A1 7/2004 (Continued)

OTHER PUBLICATIONS

More about stainless steel retreived from http://www.thomasnet.com/about/stainless-steel-80230204.html on Mar. 10, 2014.*

(Continued)

Primary Examiner — Heidi M Eide (74) Attorney, Agent, or Firm — Schwegman Lundberg & Woessner, P.A.

(57) ABSTRACT

A dental implant can include a shaft defining a longitudinal axis and having an apical end, a coronal end, and an exterior surface. A portion of the exterior surface can include a porous material. The dental implant can include at least one thread, including a non-porous material, having an interior surface and a bone-engaging surface. The interior surface can engage and wind around the exterior surface of the shaft and the bone-engaging surface can extend outwardly from the exterior surface of the shaft. The shaft can include one or more channels configured to communicate a flowable material, stored within the shaft, to the exterior surface. Each channel can include an opening at the exterior surface to release the flowable material. At least one channel can extend between a cavity of the shaft and the exterior surface and can optionally be angled toward the apical end.

18 Claims, 4 Drawing Sheets

